

# **KAAMYA INDUSTRIES**



COLORS 🌯

AREA OF USE

4 kg

white

Marble, Granite & Natural stones Granite Pietre natural

PHYSICAL STATE

**Paste** 

COLOUR

**TRANSPARENT** 

 $\mathbf{Z}$ 




### **DESCRIPTION:**

Eco Flex Plus is a high-performance adhesive designed for a wide range of flooring applications. Its eco-friendly formula provides a strong, durable bond while beingsafe for both installers and the environment. Ideal for securing vinyl, rubber, carpet tiles, and more, Eco Flex Plus ensures a firm hold with excellent flexibility toaccommodate the natural movements of flooring materials. Easy to apply and fast-setting, this adhesive simplifies installation, reducing the time and effortrequired. Choose Eco Flex Plus for a reliable and sustainable adhesive solution that delivers professional results every time.

### **Product Application Photo:**







kaamyaindustries.com

# **KAAMYA INDUSTRIES**



## **INSTRUCTIONS TO USE:**

- 1. Do not spread adhesive more than sqm at a time, Install the stone on spreadbed and continue further area.
- 2. Apply the mixed adhesive combination to the required depth (between 2-8mm) using a suitable trowel. Press the tiles gently into position with a slight twisting action, checking periodically that good contact is maintained with the back of each tile Tiles to be fixed within 15 minutes of adhesive being applied, dependin on the porosity of the surface and atmospheric conditions. Leave adequate oints between Individual wall and floor tiles. Clean off surplus adhesive from the ti e & joints.

### **HOW TO APPLYING**

- 1. MAKE STONE GRINDING WITHROUGH GRID TO MAKE LEVELLING. MAKE SURFACE CLEAN WITH WATER FOLLOW TO DRY & DUST FREE
- 2. APPLY MARBLE PRO UNIFORMLYON THE FLOOR WIPER 4-5 COATS REQUIRED **FOLLOWING SECOND**
- 3. GO AHEAD GRINDING WITH POLISHING GRIT. IT MANY REQUIRE ADDITIONAL 1-2 COAT OF MARBLE MAGIK PRO ON PRODUCTS STONE
- 4. DO FINAL POLISHING

### PRECAUTIONS AND NOTES:

**Eco-friendly adhesive for various flooring applications** Provides a strong, durable, and flexible bond Suitable for vinyl, rubber, carpet tiles, and more Easy application and fast-setting for quick installations Safe for both installers and the environment

